

**2.5G 1310nm FP TO56**

SHIJIA's 2.5G 1310nm FP TO56 uncooled, hermetically sealed, 4pin TO-56 style packages are a cost-effective means of providing a low-noise light source.

Features:

- Uncooled operation
- 1310nm 2.5G FP laser
- High stability and reliability
- TO56 package with Big Lens Cap
FL=6.6mm
- Operating case temperature: -40 to 85°C
- Qualified meet ROHS requirement

Applications:

- PON /Access /Optical Ethernet /SDH /FTTx Networks Metro Area Networks
- Data communications
- Point-to-point fiber optic links
- Other optical transmission system

**Optical and Electrical Characteristics($T_c=25^\circ C \pm 2^\circ C$, Unless otherwise noted):**

Parameter	Symbol	Min	Typ	Max	Units	Notes
Threshold Current	I _{th}		10	15	mA	CW, T _c =25°C
			20	40	mA	CW, T _c =85°C
Optical Output Power	P _o	7.8			mW	T _c =25°C I _f =I _{th} +20mA
Slope Efficiency	SE	0.39			mW/mA	T _c =25°C , I _f =I _{th} +20mA
Centre Wavelength	λ	1290	1310	1330	nm	CW, I _f =I _{th} +20mA
Optical Spectrum Width (RMS)	Δλ		2	5	nm	CW, I _f =I _{th} +20mA
Monitor Current	I _m	100		1000	uA	I _f =I _{th} +20mA
Monitor Dark Current	I _d			100	nA	V=-5V
Focal Length	FL	6.3	6.6	6.9	mm	

***Remark: Power can be optimized per customer's requirement**